

Easy IP 52 port connection cables - 750 Series

This series guarantees an IP 52 protection level according to CEI EN 60947 and CEI 60529 norms and it is consistent with all 750 Series models that come with Matrix Easy port connection.

Protection rates of Easy IP 52 port connection cables follow:

Protection rate of coverings against solid bodies and water

5	Protected against dust	Dust penetration is not totally excluded but dust must not penetrate in such a quantity that could damage the good working of the equipment or jeopardise its safety.
2	Protected against vertical fall of water drops with an inclination of the covering until 15°.	The water drops which fall vertically must not cause damaging effects when the covering is inclined until 15° in comparison with its vertical position.

Characteristics of IP 52 cable - UL 1569 norms

Type of port connection on valve	Matrix Easy 6 poles
Threads diameter	1.4 mm
Conductor diameter	AWG 24
Maximum temperature use	105° C
Insulation	300 Volt
Covering threads	PVC (polyvinyl chloride)

How to order Easy IP 52 port connection cables - Available lengths

Ending with soldered threads cable - 2, 4 and 8 electrical control valves

Cable length	2 Controls	4 Controls	8 Controls
500 mm	cod. 868.870 C	cod. 868.871 D	cod. 868.872 E
1.000 mm	cod. 868.873 F	cod. 868.875 H	cod. 868.877 J
2.000 mm	cod. 868.874 G	cod. 868.876 I	cod. 868.878 K
3.000 mm	cod. 868.845 D	cod. 868.880 M	cod. 868.881 N

Easy IP 52 port connection cable (IP protection according to CEI EN 60947 and CEI 60529 norms)

